

**UNIVERSITY OF THE PHILIPPINES BAGUIO**

Governor Pack Road, Baguio City, Benguet, CAR  
 VAT Reg. TIN: 000-864-006-00007  
 Telephone No. 074.442.3484  
 Email Address: [spm0.upbaguio@up.edu.ph](mailto:spmo.upbaguio@up.edu.ph)

**REQUEST FOR QUOTATION (RFQ)**

PROCUREMENT PROJECT: Supply and Delivery of Photographic Equipment and Accessories for CS  
 Purchase Request No.: 14520; 14724  
 Approved Budget for the Contract: Php 96,996.00

Date: 29 June, 2021  
 RFQ No.: 2144  
 MOP: NP-SVP

**INSTRUCTIONS:**

- Accomplish this RFQ correctly and completely.
- Bidder should attach a copy of the latest Mayor's/ Business Permit, PhilGEPS Registration and Omnibus Sworn Statement.**
- Failure to comply with any of the Technical Specifications will disqualify the quotation.
- Submit your quotation at the Supply and Property Management Office, UP Baguio OR may email at [jebagsic@up.edu.ph](mailto:jebagsic@up.edu.ph) and cc: [spm0.upbaguio@up.edu.ph](mailto:spm0.upbaguio@up.edu.ph) with RFQ No. as part of the subject NOT LATER THAN 5:00 PM on 06 July, 2021.**
- Failure to follow these instructions will disqualify your entire quotation.

Please quote your lowest government price (including VAT) on the item/s listed below, and state the time of which you can make delivery. The information stated below shall be the basis for the evaluation and calculation of your quotation.

RODOLFO T. SOYAT, JR.  
 Chief, SPMO

ITEM NO.	GENERAL DESCRIPTION	STATEMENT OF COMPLIANCE TO TECHNICAL SPECIFICATIONS (PLEASE CHECK)		UOM	QTY	UNIT PRICE	TOTAL PRICE	QUOTED UNIT PRICE	TOTAL QUOTED PRICE	
		YES	NO							
		1	Camera AF Modes: One-Shot AF, AI Servo AF, AI Focus AF AF Point Selection: Automatic selection, Manual selection AF System Points: 9-point (Cross-type AF sensitive to f/5.6 with center AF point) Built-in Flash: YES (see full specs)							
2	Condenser Microphone with atleast 3.5mm stereo plug/cable, with ball-type foam cap, scissor arm stand (360 degree flexible, max load of atleast 2kg) with shock mount and compatible audio voice changer network live broadcast transmission vid			un	1	2,500.00	2,500.00			
3	Portable Power Station Battery Type • Lead-acid Battery Capacity • 40000mAh 800W Power Inverter Output • Three 5V 2.1A USB Sockets • One 12V DC Sockets • Two 220V AC Outlet			un	4	14,999.00	59,996.00			
4	Video lights and accessories Dimmable Bi-color Light Panel: with 330 white and 330 yellow L-ED long lasting bulbs, back with 2 control knobs to adjust brightness (0%-100%), 3200K-5600K color temperature with U bracket and accessories			un	1	4,500.00	4,500.00			
	-Delivery Period: within 30 calendar days upon receipt of Purchase Order									
	-PLEASE INDICATE WARRANTY OFFERED FOR THE ITEM									
	-*** Nothing Follows ***-									
<b>TOTAL:</b>							<b>96,996.00</b>	<b>BID TOTAL:</b>		
<b>TOTAL QUOTED AMOUNT IN WORDS:</b>										

After having carefully read and accepted your General Conditions, I/We quote you on the Item at prices noted above.

Name of the Company: \_\_\_\_\_  
 Address: \_\_\_\_\_  
 Name of Representative: \_\_\_\_\_  
 Position: \_\_\_\_\_  
 Signature: \_\_\_\_\_

Tel. No. : \_\_\_\_\_  
 Fax No. : \_\_\_\_\_  
 Email Address: \_\_\_\_\_  
 Date: \_\_\_\_\_



## Camera

**AF Modes:** One-Shot AF, AI Servo AF, AI Focus AF  
**AF Point Selection:** Automatic selection, Manual selection  
**AF System Points:** 9-point (Cross-type AF sensitive to f/5.6 with center AF point)  
**Built-in Flash:** YES  
**Closest Focusing Distance (cm):** 25  
**Continuous Shooting Speed (Shots Per Sec) (Up To):** 3  
**Digital Zoom:** -  
**Dimensions (Excl. Protrusions) (mm) (Approx.):** 129.0 x 101.3 x 77.6  
**Drive System:** Micro Motor  
**Effective ISO:** 100 - 6400 (H:12800)  
**Effective Pixels (Megapixels):** 24.1  
**Exposure Compensation:** Manual:  $\pm 5$  stops in 1/3- or 1/2-stop increments, AEB:  $\pm 2$  stops in 1/3- or 1/2-stop increments  
**Flash Modes:** E-TTL II Autoflash, FE Lock, Auto pop-up, Retractable, Built-in  
**Focal Length (35mm Equivalent):** 28.8 - 88mm(3x)  
**Guide Number ISO 100 metres:** 9.2/30.2  
**Image Resolution:** 6000 x 4000 (L) 3984 x 2656 (M) 2976 x 1984 (S1) 1920 x 1280 (S2) 720 x 480 (S3) 6000 x 4000 (RAW)  
**Image Stabilizer:** Lens-shift type  
**LCD Monitor (Size) (Inch):** 3.0  
**LCD Monitor Resolutions (dots):** 920000  
**Manual Focus:** YES  
**Memory Card Type:** SD, SDHC\*, SDXC\*, \*UHS-I cards compatible  
**Metering Mode:** 63-zone TTL Evaluative, Partial, Spot, Centre-weighted average  
**Movie Format:** MOV  
**Optical Zoom:** 3x  
**Optional Power:** AC Power (Compact Power Adapter CA-PS700 and DC Coupler DR-E10)  
**Peripheral Connections:** Hi-Speed USB, HDMI (Type C)  
**Processor Type:** DIGIC 4+  
**Sensor Size:** APS-C  
**Shooting Modes:** Scene Intelligent Auto, Flash Off, Creative Auto, Portrait, Landscape, Close-up, Sports, Food, Night Portrait, Program AE, Shutter-priority AE, Aperture-priority AE, Manual exposure  
**Shutter Speed Range (Sec.):** 30 - 1/4000, Bulb  
**Standard Power Supply:** Battery Pack LP-E10  
**Still Image Format:** JPEG, RAW, RAW + JPEG  
**Viewfinder Coverage (Approx.):** 95  
**Viewfinder Type:** Eye-level pentamirror  
**Weight (g) (Including the battery and memory card) (Approx.)**  
**\*For camera kits, weight includes kit lens(es):** 675  
**White Balance:** Auto (Ambience priority), Auto (White priority), Preset (Daylight, Shade, Cloudy, Tungsten light, White fluorescent light, Flash), Custom White balance correction, and White balance bracketing provided \* Flash color temperature information transmission possible  
**X-sync (sec.):** 1/200



## Condenser Microphone

with atleast 3.5mm stereo plug/cable, with ball-type foam cap, scissor arm stand (360 degree flexible, max load of atleast 2kg) with shock mount and compatible audio voice changer network live broadcast transmission video soundcard

Specification:

- Sensitivity: -38dB+/-2dBA
- Minimize background noise
- Wide frequency response (20Hz-20KHz)
- Compatible with Windows 10, Mac OS and Linux

## Keyboard and mouse

Keyboard Minimum Specifications:

Layout - 104-key US English QWERTY Full-size  
Connectivity - Wired  
Interface - USB

Mouse Minimum Specifications:

Tracking Technology - Optical  
Sensor Resolution - 1000  
Others - With Scroll wheel

## Writing table/slate

Specifications:

**Pen Technology: Active Electromagnetic Resonance**  
**Press Keys: 6 Programmable Press Keys**  
**Function Keys**  
**Featured Function: Touch Pad**

## Video lights and accessories

Dimmable Bi-color Light Panel: with 330 white and 330 yellow L-ED long lasting bulbs, back with 2 control knobs to adjust brightness (0%-100%), 3200K-5600K color temperature with U bracket  
Excellent quality of aluminum alloy and can be used for outdoors  
with accessories:

Adjustable Light Stand (height range 58 cm to 200 cm) with solid locking capabilities  
2 types of power supply – batteries and adapter

## HD webcams

Specifications:

- HD resolution
- 1080p recording
- 720p live video calling