

DSLR CAMERA with LENS

AF Modes: One-Shot AF, AI Servo AF, AI Focus AF, Servo AF

AF Point Selection: Automatic selection, Manual selection

AF System Points: OVf: 9 AF Points | Live View: 3,975 selectable focus positions

Built-in Flash: YES

Closest Focusing Distance (cm): 25

Continuous Shooting Speed (Shots Per Sec) (Up To): OVf: 5(One-Shot AF & AI Servo AF) | Live View:
5(One-Shot AF), 3.5(Servo AF)

Digital Zoom: Approx. 3x - 10x (movie only)

Dimensions (Excl. Protrusions) (mm) (Approx.): 122.4 x 92.6 x 69.8

Drive System: Stepping Motor-driven lead screw + rack system

Effective ISO: 100 - 25600 (H:51200)

Effective Pixels (Megapixels): 24.1

Exposure Compensation: Manual: $\pm 5^*$ stops in 1/3- or 1/2-stop increments, * ± 3 stops with [Shooting screen: Guided] set AEB: ± 2 stops in 1/3- or 1/2-stop increments

Eye Detection AF: Live View: One-Shot AF & Servo AF

Flash Modes: E-TTL II Autoflash, FE Lock, Manual pop-up, Retractable, Built-in

Focal Length: (35mm Equivalent) 28.8 - 88mm(3x)

Guide Number ISO 100 metres: 9.8/32.1

Image Resolution: 6000 x 4000 (L) 3984 x 2656 (M) 2976 x 1984 (S1) 2400 x 1600 (S2) 6000 x 4000
(RAW/C-RAW)

Image Stabilizer: Lens-shift type

LCD Monitor (Size) (Inch): 3.0

LCD Monitor Resolutions (dots): 1,040,000

Manual Focus: YES

Memory Card Type: SD, SDHC*, SDXC*, *UHS-I cards compatible

Metering Mode: 63-zone TTL Evaluative, Partial, Spot, Centre-weighted average

Movie Format: MP4

Optical Zoom: 3x

Optional Power: AC Power (AC Adapter AC-E6N and DC Coupler DR-E18)

Peripheral Connections: Hi-Speed USB, Audio / Video Output, HDMI (Type C) / Microphone / Remote

Processor Type: DIGIC 8

Sensor Size: APS-C

Shooting Modes: Scene Intelligent Auto, Special scene modes (Portrait, Smooth Skin, Group Photo, Landscape, Sports, Kids, Close-up, Food, Candlelight, Night Portrait, Handheld Night Scene, HDR Backlight Control), Creative filters (Grainy B/W, Soft focus, Fish-eye effect, Water painting effect, Toy camera effect, Miniature effect, HDR art standard, HDR art vivid, HDR art bold, HDR art embossed), Program AE, Shutter-priority AE, Aperture-priority AE, Manual exposure

Shutter Speed Range (Sec.): 30 - 1/4000, Bulb

Standard Power Supply: Battery Pack LP-E17

Still Image Format: JPEG, RAW, C-RAW, RAW + JPEG, C-RAW + JPEG

Viewfinder Coverage (Approx.): 95%

VIDEO CAMERA with ACCESSORIES